Porcelain Stone®

Available Colors



JAV01 ▶ Two Sugars



JAV03 ▶ House Blend



JAV05 ▶ French Press



JAV02 ▶ Flat White



JAV04 ▶ Fresh Ground

Features and Benefits

- Striations of crema and bold neutrals present a product line that is steeped in versatility.
- Color and graphics blend to perfection in 5 tones, sized perfectly in 12 x 24 to suit the superior tastes of any design barista
- Available with bullnose, cove base, and 2 x 2 mosaics
- Competitively priced for exceptional value
- · Cross-Sheen finish for easy cleaning
- · Made in the USA

Porcelain Stone®

Available Mosaics



JAV01 ▶ Two Sugars 2 x 2 Mosaics



JAV02 ▶ Flat White 2 x 2 Mosaics



JAV03 ► House Blend 2 x 2 Mosaics



JAVO4 ▶ Fresh Ground 2 x 2 Mosaics



JAV05 ▶ French Press 2 x 2 Mosaics



Porcelain Stone®

Sizes (Shown in JAV02)





2 x 2 Mosaics UPS Finish (Mounted on an 12 x 12 sheet.)

Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum _____

order and quick fulfillment.
See website for more details

and sizes.



Sizes & Finishes

4	Field Tile - Calibrated		Available in all	colors	
	Nominal (in)	Actual (in)	Thickness (in)	Grout Joint (in)	Finish
	12 x 24	11-13/16 x 23-13/16	3/8	3/16	UPS

All field tile is calibrated (non-rectified).

Crossville recommends a minimum 3/16" grout joint.

4	Mosaics	losaics		Available in all colors		
	Nominal (in)	Actual (in)	Thickness (in)	Grout Joint (in)	Finish	
	2 x 2 Mosaic	11-3/4 x 11-3/4	3/8	3/16	UPS	

^{*} Mounted on 11-3/4 x 11-3/4 sheets.

Coordinating Trim

Т	Nominal (mm)	Actual (in)	Thickness (in)	Grout Joint (in)	Finish
	4 x 24 Single Bullnose	3-13/16 x 23-13/16	3/8	3/16	UPS
	6 x 12 Cove Base	5-7/8 x 11-3/4	3/8	3/16	UPS



6 x 12 Cove Base

Product Performance


Breaking Strength	>450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.50%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

	0.40.0.50	
UPS	0.42 - 0.52	ANSI A326 3

Shade & Texture Index

Java Joint has a shade variation of V2.



V1 Uniform appearance V2 Slight Variation

V3 Moderate Variation V4 Substantial Variation

This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

Application Areas

Finish	Interior Floors (dry)	Interior Walls (wet/dry)	Exterior Walls	Interior Floors (Standing water/ shower floors)	Exterior/Paving	Pool/Fountain Full Lining**	Water Line Pool/ Fountains
UPS	✓	✓	✓	Mosaics Only*		✓	✓

 $^{^{\}ast}~4\text{"}$ or less in both length and width, UPS or UP mosaics

NOTE: Trim applications will differ from field tile applications for the same series.

For more information on ANSI- A362.3 visit our website at https://www.crossvilleinc.com/Resources/Tile-101/DC0F?tab=1



^{**} Excludes mesh mounted mosaics. Crossville recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Crossville sales representative for more information.

Crossville, Inc.

PO Box 1168 Crossville, TN 38557 Phone 931.484.2110 Fax 931.456.2956

E-Mail Crossc@CrossvilleInc.com

Web CrossvilleInc.com

Recommended Use

Java Joint is recommended for interior floors, interior walls, countertops, exterior walls, pool waterlines and full linings† in both residential and commercial applications. Java Joint is not recommended for exterior horizontal surfaces or exterior paving. See CrossvilleInc.com for detailed installation instructions.

†Excludes mesh mounted mosaics.

Care and Maintenance

Regular cleaning is the best way to keep Java Joint tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville products is available at CrossvilleInc.com.

Our Warranty

Crossville Inc guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2022 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc. com for the latest, most accurate information

Crossville® Sample Express

Visit the website to learn more:

CrossvilleInc.com/Products/
Java-Joint

Loose Tile Samples

Sizes may vary depending on product series Max. of 4 large field tile per order

Standard Shipping

FedEX Ground

National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com.



Trade Organizations













Environmentally Aware





