Moonstruck

Porcelain Stone®

Colors



AV301 ▶ Juno UPS



AV301 ▶ Juno HON



AV304 ▶ Gemini UPS



AV304 ▶ Gemini HON



AV302 ▶ Luna UPS



AV302 ▶ Luna HON



AV305 ▶ Apollo UPS



AV305 ▶ Apollo HON



AV303 ▶ Kosmos UPS



AV303 ▶ Kosmos HON

Features and Benefits

- Visually replicated from the moons of our solar system in five striking shades
- Sizes offered 12 x 24 and 18 x 36 rectified tile in both unpolished and honed finishes
- Trim includes 4 x 24 single bullnose
- Green SquaredSM certified and Made in the USA
- Cross-Sheen® finish for easy cleaning
- Plank shapes are also available through Crossville's Get Planked® program, which offers a variety of plank sizes with no minimum order and a short lead time




Moonstruck

Porcelain Stone®

Sizes (Available in all colors)







AV305 ▶ Apollo 12 x 24 HON

| Sizes & Fi | nıshes |
|------------|--------|
|------------|--------|

| 4 | Field Tile - Rectified | 1 | Available in all | colors | |
|---|------------------------|-------------|------------------|------------------|---------|
| | Nominal (in) | Actual (mm) | Thickness (mm) | Grout Joint (mm) | Finish |
| | 12 x 24 | 297 x 597 | 9.5 | 3 | UPS/HON |
| | 18 x 36 | 447 x 897 | 10.5 | 3 | UPS/HON |
| | | | | | |

All field tile is calibrated (non-rectified). Crossville recommends a grout joint of 3mm

| 4 | Coordinating Trim | | Available in all | colors | |
|---|------------------------|-------------|------------------|------------------|---------|
| | Nominal (in) | Actual (mm) | Thickness (mm) | Grout Joint (mm) | Finish |
| | 4 x 24 Single Bullnose | 96 x 597 | 9.5 | 3 | UPS/HON |

4 x 24 Single Bullnose

Product Performance


| >450 lbf | ASTM C648 |
|------------|-------------------------------------|
| >200 psi | ASTM C482 |
| Unaffected | ASTM C650 |
| Resistant | ASTM C1026 |
| <0.50% | ASTM C373 |
| 7 | Mohs Scale |
| | >200 psi Unaffected Resistant |

Wet Dynamic Coefficient of Friction Range

| UPS | 0.50 - 0.60 | ANSI A326.3 |
|-----|-------------|-------------|
| HON | 0.42 - 0.52 | ANSI A326.3 |

Shade & Texture Index

Moonstruck has a shade variation of V3.



V2 Slight Variation

V3 Moderate Variation

V4 Substantial Variation

V1 Uniform appearance

This porcelain tile product is produced with a V3 variation. Expect that the amount of color and texture on each piece may vary significantly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation

Get Planked!

Our Porcelain Stone* products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



Application Areas

| Finish | Interior Floors (dry) | Interior Walls (wet/dry) | Exterior Walls | Interior Floors (Standing water/ shower floors) | Exterior/Paving | Pool/Fountain Full Lining** | Water Line Pool/ Fountains |
|--------|-----------------------|-----------------------------|-------------------|---|-----------------|--------------------------------|-------------------------------|
| UPS | ✓ | ✓ | ✓ | | | ✓ | ✓ |
| HON | ✓ | ✓ | ✓ | | | ✓ | ✓ |

^{**} Excludes mesh mounted mosaics. Crossville recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Crossville sales representative for more information.

For more information on ANSI- A362.3 visit our website at https://www.crossvilleinc.com/Resources/Tile-101/DCOF?tab=1



NOTE: Trim applications will differ from field tile applications for the same series.

Moonstruck

Crossville, Inc.

PO Box 1168 Crossville, TN 38557

Phone 931.484.2110 Fax 931.456.2956

E-Mail Crossc@CrossvilleInc.com

Web CrossvilleInc.com

Recommended Use

Moonstruck is recommended for interior floors, interior walls, countertops, exterior walls, pool waterlines and full linings† in both residential and commercial applications. Moonstruck is not recommended for exterior horizontal surfaces or exterior paving. The honed finish is not recommended for wet areas where standing water may occur. See CrossvilleInc.com for detailed installation instructions.

† Excludes mesh mounted mosaics

Care and Maintenance

Regular cleaning is the best way to keep Moonstruck tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More Information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc. com for the latest, most accurate information.

Crossville® Sample Express

Visit the website to learn more: CrossvilleInc.com/Products/ Moonstruck

Loose Tile Samples

Sizes may vary depending on product series Max. of 4 large field tile per order

Standard Shipping

FedEX Ground

National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com.

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2022 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.



Trade Organizations



















