Multiplier

Porcelain Mosaic

Available Colors



MTP01 ▶ White 2" Square Matte



MTP01 ▶ White 2" Square Gloss



MTP02 ▶ Grey 2" Square Matte




MTP02 ▶ Grey 2" Square Gloss



MTP03 ▶ Dark Grey2" Square Matte



MTP03 ▶ Dark Grey 2" Square Gloss



MTP01 ▶ White 3/4" Penny Round Matte



MTP01 ▶ White 3/4" Penny Round Glos



MTP02 ▶ Grey 3/4" Penny Round Mat



MTP02 ▶ Grey 3/4" Penny Round Gloss



MTP03 ▶ Dark Grey 3/4" Penny Round Matte



MTP03 ▶ Dark Grey 3/4" Penny Round Gloss



MTP01 ▶ White 2" Hex Matte



MTP01 ▶ White 2" Hex Gloss



MTP02 ▶ Grey 2" Hex Matte



MTP02 ▶ Grey 2" Hex Gloss



MTP03 ▶ Dark Grey 2" Hex Matte



MTP03 ▶ Dark Grey 2" Hex Gloss



Multiplier

Porcelain Mosaic

Sizes

| Wodale The | | | | | |
|---------------------|-------------------|--------------------------|----------------|------------------|-------------|
| | Nominal Size (in) | Actual Size (mm) | Thickness (mm) | Grout Joint (mm) | Finish |
| 2" Square* | 2 x 2 | 47.5 x 47.5 | 6 | 2.6 | Gloss/Matte |
| 2" Hex** | 2 x 2 | 47.5 x 47.5 [†] | 6 | 2.6 | Gloss/Matte |
| 3/4" Penny Round*** | | 19 (diameter) | 6 | 2.0 | Gloss/Matte |

^{* 2&}quot; Square is mounted on a 301 x 301 sheet (Coverage area 0.97263 sf)

Product Performance


| Breaking Strength | >350 lbf | ASTM C648 |
|---------------------|-----------|------------|
| Chemical Resistance | Resistant | ASTM C650 |
| Water Absorption | ≤0.20% | ASTM C373 |
| Scratch Hardness | 7 | Mohs Scale |

Wet Dynamic Coefficient of Friction Range

| Gloss | <0.42 | ANSI A326.3 |
|-------|-------|-------------|
| Matte | <0.42 | ANSI A326.3 |

Shade & Texture Index

Multiplier has a shade variation of V1



V1 Uniform appearance

V2 Slight Variation

V3 Moderate Variation

V4 Substantial Variation


This porcelain tile product is produced with a V1 variation. Differences among pieces from the same production run are minimal. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

Sizes


shown in MTP02 Matte



2" Square Mosaic



3/4" Penny Round Mosaic



2" Hex Mosaic

Application Areas

| Finish | Interior Floors (dry) | Interior Walls (wet/dry) | Exterior Walls (covered) | Interior Floors (Standing water/ shower floors) | Exterior/Paving | Pool/Fountain Full Lining** | Water Line Pool/ Fountains |
|-----------------|-----------------------|-----------------------------|-----------------------------|---|-----------------|--------------------------------|-------------------------------|
| Gloss and Matte | ✓ | ✓ | ✓ | √ † | | | ✓ |

✓¹ Note: Tile selection for wet applications (such as shower or bathroom floors) requires careful consideration of the unique nature of the design and installation. For instance, the industry standard for tile used on level interior surfaces is a dynamic coefficient of friction (DCOF) value of 0.42 or greater; however, the use of small (2" or less) mosaics with lower DCOF values may nonetheless be acceptable for projects with an increased number of grout joints, along with the presence of other surface structures that provide both traction and a means for water to drain and dissipate from the area. It is the sole responsibility of each end user to consult with a design professional to determine and select the most suitable flooring for a particular project.

representative for more information.

NOTE: Trim applications will differ from field tile applications for the same series. For more information on ANSI- A362.3 visit our website at https://www.crossvilleinc.com/Resources/Tile-101/DCOF?tab=1



^{** 2&}quot; Hex is mounted on a 272 x 326 sheet (Coverage area 0.83894 sf)

^{*** 3/4&}quot; Penny Round is mounted on a 292 x 324 sheet (Coverage area 0.99617 sf)

 $[\]dagger$ 2" Hex tile measures 47.5mm from one straight edge to the opposing parallel edge

^{**} Excludes mesh mounted mosaics. Crossville recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Crossville sales representative for more information

Multiplier

Crossville, Inc.

PO Box 1168 Crossville, TN 38557 **Phone** 931.484.2110 **Fax** 931.456.2956

E-Mail Crossc@CrossvilleInc.com

Web CrossvilleInc.com

Features and Benefits

- Three colors and three shapes, this concise offering quickly expands with possibility
- 2" Square, 3/4" Penny Round and 2" Hexagon mesh mounted mosaic for easy installation
- Attractively priced, grow your creativity, without growing your budget.
- Multiplier can help grow your creativity, without growing your budget

Care and Maintenance

Regular cleaning is the best way to keep Multiplier tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Recommended Use*

Multiplier tile is recommended for Interior Floors Dry, Interior Walls Dry, Interior Walls Wet, Exterior Walls, Exterior Covered Walls, Waterline Pool/ Fountain, Countertops in residential and commercial applications.

* The tile applications featured in this publication are for illustration purposes only and are not intended as a representation or warranty of the suitability of Crossville Tile for any particular application. Specifically, tile selection for wet applications (such as shower or bathroom floors) requires careful consideration of the unique nature of the design and installation. For instance, the industry standard for tile used on level interior surfaces is a dynamic coefficient of friction (DCOF) value of 0.42 or greater: however, the use of small (2" or less) mosaics with lower DCOF values may nonetheless be acceptable for projects with an increased number of grout joints, along with the presence of other surface structures that provide both traction and a means for water to drain and dissipate from the area. It is the sole responsibility of each end user to consult with a design professional to determine and select the most suitable flooring for a particular project.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

Crossville Sample Express

Visit the website to learn more: CrossvilleInc.com/Products/Multiplier

Loose Tile Samples

Sizes may vary depending on product series
Max. of 4 large field tile per order

Standard Shipping

FedEX Ground

National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com.

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com

Trade Organizations















