Native Metal Porcelain Stone®



Available Colors



NVM01 ► Noble Platinum



NVMO3 ► Crucible Steel



NVM05 ►Cobalt Ore

Features and Benefits

- Native Metals captures the eternal luxury of patinaed minerals and ores in a refreshingly unique porcelain and resin tile line.
- Unpolished Rectified field tile sizes: 12"x 24", 24"x 24" and 24"x 48"
- 2"x2" and mixed hex mosaic with 2"x 12" metallic deco.
- Complete your installations with 4"x 24" bullnose or 6"x 12" cove base
- Cross-Sheen® for easy cleaning
- Made in the USA and Green Squaresm Certified



NVM02 ► Nickel Plate



NVMO4 ► Copper Deposit



NVM06 ► Graphite Black



Native Metal Porcelain Stone®



Available Mosaics




NVM01.10202MOS Noble Platinum 2 x 2 Mosaic



NVM01.1HEXGMOS Noble Platinum with Gold Mixed Hex Mosaic



NVM05.1HEXIMOS Cobalt Ore with Iron Mixed Hex Mosaic





NVM01.1HEXIMOS Noble Platinum with Iron Mixed Hex Mosaic



NVM06.1HEXIMOS Graphite Black with Iron Mixed Hex Mosaic



Crucible Steel 2 x 2 Mosaic



NVM02.1HEXIMOS Nickel Plate with Iron Mixed Hex Mosaic



Copper Deposit 2 x 2 Mosaic



NVM03.1HEXIMOS Crucible Steel with Iron Mixed Hex Mosaic



NVM05.10202MOS Cobalt Ore 2 x 2 Mosaic



Copper Deposit with Gold Mixed Hex Mosaic



NVM06.10202MOS Graphite Black 2 x 2 Mosaic



NVM04.1HEXIMOS Copper Deposit with Iron Mixed Hex Mosaic



Native Metal Porcelain Stone[®]

Sizes (Available in all colors)









Mosaic (Mounted on a 298 x 298 mm sheet)

2 x 12 Perforated Deco

259 x 270 mm sheet) 2 x 12 Molten

Deco

Mixed Hex

(Mounted on a

Mosaic[†]

Sizes & Finishes

•				
Field Tile - Rectified			Available in all colors	
Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
12 x 24	297 x 597	9.5	3	UPS
24 x 24	597 x 597	9.5	3	UPS
24 x 48	597 x 1197	10.5	3	UPS
	Nominal (in) 12 x 24 24 x 24	Nominal (in) Actual (mm) 12 x 24 297 x 597 24 x 24 597 x 597	Nominal (in) Actual (mm) Thickness (mm) 12 x 24 297 x 597 9.5 24 x 24 597 x 597 9.5	Nominal (in) Actual (mm) Thickness (mm) Grout Joint (mm) 12 x 24 297 x 597 9.5 3 24 x 24 597 x 597 9.5 3

Note: Field tile is rectified with a 3mm grout joint

Deco	1			
Nominal (in)	Sheet Size (mm)	Thickness (mm)	Grout Joint (mm)	Finish
2 x 12 Metalic Deco	47 x 297	9.5	3	SAT

Mosaics			Available in all colors	
Nominal (in)	Sheet Size (mm)	Thickness (mm)	Grout Joint (mm)	Finish
2 x 2 Mosaic*	298 x 298	9.5	3	UPS
Mixed Hex Mosaic	259 x 270	9.5	2	UPS

*Mounted on 298mm x 298mm sheet with 3mm grout joints (Coverage area 0.9752 sf) **Mounted on 259mm x 270 sheet with 2mm grout joints (Coverage area 0.61 sf)

Nominal (in) Actual (mm) Thickness (mm) Grout Joi	int (mm) Finish
4 x 24 Single Bullnose 96 x 597 9.5 3	UPS
6 x 12 Cove Base 150 x 297 9.5 3	UPS

4 x 24 Single Bullnose

	7			
6	Х	12	Cove	Base

≥450 lbf	ASTM C648
>200 psi	ASTM C482
Unaffected	ASTM C650
Resistant	ASTM C1026
<0.50%	ASTM C373
7	Mohs Scale
	>200 psi Unaffected Resistant

Get Planked!

Our Porcelain Stone[®] products are available in popular plank shapes with no minimum order and quick fulfillment. See website for more details and sizes.




Wet Dynamic Coefficient of Friction Range UPS

0.50 - 0.60

ANSI A326.3

Shade & Texture Index

Native Metal has a shade variation of V3.



This porcelain tile product is produced with a V3 variation. While the colors and/or textures present on a single piece of tile will be indicative of the colors and/or textures to be expected on the other tiles, the amount of colors and/or texture on each piece may vary significantly. It is recommended that the range be viewed before selection.



Native Metal

Crossville, Inc.

PO Box 1168 Crossville, TN Phone 931.484.2110 931.456.2956 Fax E-Mail Crossc@CrossvilleInc.com Web CrossvilleInc.com

Application Areas

Finish	Interior Floors (dry)	Interior Walls (wet/dry)	Exterior Walls	Interior Floors (Standing water/ shower floors)	Exterior/Paving	Pool/Fountain Full Lining**	Water Line Pool/ Fountains
UPS	\checkmark	√*	\checkmark			\checkmark	\checkmark

* The 2 x 12 mosaic can be used in linear drain shower pans as long as the 12 inch side runs parallel to the drain.

** Excludes mesh mounted mosaics. Crossville recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Crossville sales representative for more information. NOTE: Trim applications will differ from field tile applications for the same series.

For more information on ANSI- A362.3 visit our website at https://www.crossvilleinc.com/Resources/Tile-101/DCOF?tab=1

Recommended Use

Native Metal is recommended for interior floors, interior walls, countertops, exterior walls, pool waterlines and full linings[†] in both residential and commercial applications. Native Metal is not recommended for exterior horizontal surfaces or exterior paving. The Mixed Hex Mosaics and the 2 x 12 Deco pieces are to be used on interior walls only. See CrossvilleInc.com for detailed installation instructions.

+ Excludes mesh mounted mosaics.

Wet area use for Native Metal Mosaics

Crossville[®] produces the Native Metal 2 x 2 mosaics with the Cross-Sheen (UPS) finish. The ANSI A326.3 wet Dynamic COF of Native Metal is ≥ 0.42 . Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning. This information is provided so that customers may make a realistic and informed decision when comparing Native Metal to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

Care and Maintenance

Regular cleaning is the best way to keep Native Metal tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

Crossville[®] Sample Express

Visit the website to learn more: CrossvilleInc.com/Products/ Native-Metal

Loose Tile Samples

Sizes may vary depending on product series Max. of 4 large field tile per order

Standard Shipping FedEx Ground

CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com. Information listed here is subject to change.

Trade Organizations





Environmentally Aware







